



The PAR20 LED SSL replacement lamp provides equivalent lighting to a 50W Incandescent or a 30W Halogen lamp. Our unique thermal design and driver technology provide equivalent or better lumen output while consuming only 20% of electricity than most efficient light sources today. The PAR 20 high power, high efficiency LED design consumes only 7W of electricity.

- Features:
 Designed as a direct retrofit to most PAR 20 lighting fixtures
 No UV or IR
 Edison Base
 7W power consumption
 Long life=Labor Savings
 30,000 hours rated life to 70% of initial light output
 CRI-82

Part NO	Voltage	CCT	Lumen	Power	Housing Temp
PAR20C9W	110/220V	2800K	268	7W	55 C
		3000K			
		3200K			
		3500K			
PAR20C9W	110/220V	5500K	310	7W	55 C
		6000K			
		6500K			

Note: Available full angle: 15/ 25/ 40 /60 / 80 /

Photometric

Throw Distance (M)	PAR20C9WC5-25		PAR20C9WW3-25		PAR20C9WC5-40		PAR20C9WW3-40	
	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)
1	29	4494	29	3595	53	2830	53	1870
2	41	1147	41	899	67	710	67	470
3	63	524	63	399	90	315	90	210

