



Our PAR30 LED SSL replacement lamp is a true representation of what the future of LED lighting holds. Its unique thermal design allows for the best heat dissipation possible in a direct retrofit PAR 30 foot print. Its high efficiency LED replaces up to 75W Incandescent or 50-60W Halogen lamp. Using only 15W or less of power it is able to illuminate up to a distance of more than 10 meters

- Features:
- Designed as a direct retrofit to most PAR30 lighting fixtures
 - No UV or IR
 - Edison Base with wide beam angle selection
 - 15W power consumptions
 - Long life=Labor Savings
 - 30,000 hours rated life to 70% of initial light output
 - CRI-82

Part NO	Voltage	CCT	Lumen Output	Power Consumpt ion	Housing Temp
		2800K			
PAR30C15WW3	110/220V	3000K			
		3200K	483	13W	63 C
		3500K			
		5500K			
		6000K		13W	63 C
PAR30C15WC5	110/220V	6500K	525		

Note: Available full beam angle: 15 / 25/ 40 / 60 / 80 /

Photometric

	PAR30C15WC5-15		PAR30C15WW3-15		PAR30C15WC5-40		PAR30C15WW3-40	
Throw Distance (M)	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)	Beam width (cm)	Luminance (lux)
1	40	8237	48	6739	73	1050	73	960
2	68	2982	68	1685	108	263	108	250

